



### 电气参数 Electrical:

输出形式 Output Mode	集电极开路输出 Open Collect Output	电压输出 Voltage Output	互补输出 Complementary Output	长线驱动输出 Drive Element Output
使用电压 Power Source	5-26V	5 V±0.25 5-26V	5V±0.25 5-26V	5V±0.25 5-26V
输出电压 Output Voltage	“1” >0.7Vcc		“0” <0.1Vcc	
输出信号 Signal Mode	A B	A B	A B	A B /A /B
消耗电流 Current Consumption	≤80mA	≤80mA	≤80mA	≤150mA
信号升降时间 Signal Rising & Falling Time	<1.5us			
工作频带 Scanning Frequency	0.....100kHz			

### 机械参数 Mechanical:

起动力矩 Starting Torque	<1.96X10 <sup>-3</sup> Nm
轴负荷 Shaft loading	轴向 Radial 30N, 径向 Thrust 60N
最大转速 Max Slewing Speed	6000r/min
重量 Weight	250g

### 环境条件 Environmental:

工作温度 Operating Temperature	-10~+60°C
储存温度 Storage Temperature	-20~+80°C
耐冲击 Vibration	30G 11ms
耐震动 Shock	50Hz 1h

### 外形尺寸 Dimensions:

